Material Safety Data Sheet



ECOTEMP ULTRA KLENE

Section 1. Chemical product and company identification

Trade name : ECOTEMP ULTRA KLENE
Product use : Machine Warewashing Detergent
Supplier : Ecolab Inc. Institutional Division

370 N. Wabasha Street St. Paul, MN 55102 1-800-352-5326

 Code
 : 986216-02

 Date of issue
 : 10-May-2006

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, information on ingredients

NameCAS number% by weightsodium hydroxide1310-73-223

Section 3. Hazards identification

Physical state Emergency

: Liquid. : DANGER!

Emergency overview

CAUSES EYE AND SKIN BURNS.

CAUSES SEVERE RESPIRATORY TRACT IRRITATION.

HARMFUL IF SWALLOWED.

Do not ingest. Do not get in eyes, on skin or on clothing. Avoid breathing vapor or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Potential acute health effects

Eyes : Corrosive to eyes.

Skin : Corrosive to the skin.

Inhalation: Severely irritating to the respiratory system.

Ingestion: Harmful if swallowed. Causes burns to mouth, throat and stomach.

See toxicological information (section 11)

Section 4. First aid measures

Eye contact: In case of contact, immediately flush eyes with cool running water. Remove contact lenses and

continue flushing with plenty of water for at least 15 minutes. Get medical attention

immediately.

Skin contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes

thoroughly before reuse. Get medical attention immediately.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult,

give oxygen. Get medical attention immediately.

Ingestion: Rinse mouth; then drink one or two large glasses of water. Do not induce vomiting. Never give

anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire fighting measures

Flash point : > 100°C

Product does not support combustion.

Fire-fighting media and

instructions

: Use an extinguishing agent suitable for the surrounding fire.

Dike liquid for later disposal.

No specific hazard.

Special protective equipment:

for fire-fighters

ECOTEMP ULTRA KLENE Page: 2/4

> Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

Section 6. Accidental release measures

Personal precautions : Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Do not allow to enter drains or watercourses.

Environmental precautions Methods for

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

cleaning up

: If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Section 7. Handling and storage

Handling

: Do not ingest. Do not get in eyes, on skin or on clothing. Keep container closed. Do not allow water to enter container. Use only with adequate ventilation. Do not breathe vapor or mist. Wash thoroughly after handling. Do not add water directly to product. Slowly stir product into water.

SAFETY REMINDER:

- * Never pour product into unlabeled containers * Use only for recommended uses. Read label.
- * Never take product home. Use only in workplace.

Storage

: Keep out of the reach of children. Keep container tightly closed. Keep container in a cool, wellventilated area.

Do not store above 50°C

Section 8. Exposure controls, personal protection

Engineering controls

: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Provide eyewash and safety shower in area if contact or splash hazard exists.

Personal protection

Eyes

: Use chemical splash goggles. For continued or severe exposure wear a face shield over the

Hands

: Use chemical-resistant, impervious gloves.

Skin

: Use synthetic apron, other protective equipment as necessary to prevent skin contact.

Respiratory

: Wear appropriate respirator when ventilation is inadequate and occupational exposure limits

are exceeded.

Name

Exposure limits

sodium hydroxide

OSHA PEL (United States, 8/1997). TWA: 2 mg/m³ 8 hour(s). Form: All forms ACGIH TLV (United States, 1/2004).

CEIL: 2 mg/m³

CEIL: 2 mg/m³ Form: All forms

Section 9. Physical and chemical properties

Liquid. Physical state : Red. (Dark.) Color : Odorless. Odor : 13.5 (100%) : 1.275 (Water = 1) Specific gravity

Solubility : Easily soluble in cold water, hot water. ECOTEMP ULTRA KLENE Page: 3/4

Section 10. Stability and reactivity

Stability : The product is stable. **Reactivity** : Highly reactive with acids.

Section 11. Toxicological information

Potential acute health effects

Eyes : Corrosive to eyes.

Skin : Corrosive to the skin.

Inhalation: Severely irritating to the respiratory system.

Ingestion : Harmful if swallowed. Causes burns to mouth, throat and stomach.

Chronic effects on

: Contains material which causes damage to the following organs: lungs, upper respiratory

humans tract, skin, eye, lens or cornea.

Section 12. Ecological information

Products of degradation: These products are carbon oxides (CO, CO₂) and water, phosphates. Some

metallic oxides.

Section 13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of

spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority

requirements.

Waste : Unused product is D002 (Corrosive)

classification

Consult your local or regional authorities.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
DOT Classification	UN1824	Sodium hydroxide solution	8	II	Limited quantity Yes. Special provisions
					Special provisions B2, IB2, N34, T7, TP2

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

Section 15. Regulatory information

HCS Classification : Corrosive material

Target organ effects

U.S. Federal regulations : SARA 302/304/311/312 extremely hazardous substances: No products were

found

SARA 302/304 emergency planning and notification: No products were found.

TSCA 8(b) inventory: All materials are listed or exempt.

California Prop. 65 : No products were found.

ECOTEMP ULTRA KLENE Page: 4/4

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health * 3
Fire hazard 0
Reactivity 0
Personal protection C

Date of issue : 10-May-2006.

Responsible name : Regulatory Affairs

Date of previous issue : 10-February-2006.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.