

KRYLON DEPT.,DIV.OF BORDEN CHEMICAL,BORDEN INC. -- 1401 BRIGHT SILVER,
17178,SPRAY PAINT -- 8010-00-397-2983

=====
Product Identification
=====

Product ID:1401 BRIGHT SILVER, 17178,SPRAY PAINT
MSDS Date:01/01/1985
FSC:8010
NIIN:00-397-2983
MSDS Number: BDXNN
=== Responsible Party ===
Company Name:KRYLON DEPT.,DIV.OF BORDEN CHEMICAL,BORDEN INC.
Address:630 E WASHINGTON
Box:390
City:NORRISTOWN
State:PA
ZIP:19404
Country:US
CAGE:JO900

=== Contractor Identification ===
Company Name:KRYLON DEPT.,DIV OF BORDEN CHEM.,BORDEN INC.
Address:630 E WASHINGTON
Box:390
City:NORRISTOWN
State:PA
ZIP:19404
Country:US
CAGE:JO900
Company Name:KRYLON PRODUCTS
Address:31500 SOLON ROAD
Box:City:SOLON
State:OH
ZIP:44139
Country:US
Phone:800-832-2541/216-566-2917
CAGE:87187

=====
Composition/Information on Ingredients
=====

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 40%
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:HEXANE (N-HEXANE)
CAS:110-54-3
RTECS #:MN9275000
Fraction by Wt: 19%
OSHA PEL:500 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 18%
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 9.0%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:SE7555000
Fraction by Wt: 7.0%
OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overexposure:LIGHTHEADEDNESS,DIZZY,HEADACHE,FATIGUE,MUSCULAR
WEAKNESS,MENTAL CONFUSION,NAUSEA,INSOMNIA

=====
First Aid Measures
=====

First Aid:INHAL:MOVE TO FRESH AIR.IF SPRAYED IN EYES,FLUSH WITH WATER.

=====
Fire Fighting Measures
=====

Extinguishing Media:DRY CHEM
Fire Fighting Procedures:NORMAL CLASS B FIRE PROCEDURES
Unusual Fire/Explosion Hazard:IF SPRAYED WITHIN 12 IN.OF OPEN FLAME
SPRAY MAY IGNITE & BURN LIKE A BLOWTORCH

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE SOURCES OF IGNITION.SOAK UP WITH
ABSORBENT MATERIAL VENTILATE AREA. MATERIAL NOT DANGEROUS WHEN
SOLVENTS HAVE EVAPORATED. (MFG)

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE OVER 120F.DO NOT PLACE
CAN ON RADIATOR,STOVE,DIRECT SUNLIGHT OR NEAR OTHER HEAT SOURCES.
Other Precautions:DO NOT PUNCUTRE OR INCINERATE CONTAINER.IF BURNED DO
NOT BREATH FUMES.USE AIR PACK TO AVOID PYROLYSIS PRODUCT

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:VENTILATE ADEQUATELY
Ventilation:AS NEEDED TO KEEP AREA BELOW ESTIMATED TLV.
Supplemental Safety and Health
VAPOR DENSITY IS UNKNOWN; SPRCIFIC GRAVITY IS < WATER. ADD
INGRED:ACRYLIC-VINYL TOLUENE, SOYA ALKYD, DRIERS, 3.9%; ALUMINUM,
3.7%.

=====
Physical/Chemical Properties
=====

HCC:V3
Vapor Density:UNK.
Spec Gravity:1 BUAC
Solubility in Water:SLIGHT
Percent Volatiles by Volume:93.0

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:COMBUSTION MAY PRODUCE TOXIC &

IRRITATING CHLORINE COMPOUNDS

===== Disposal Considerations =====

Waste Disposal Methods:WHEN DRY DISPOSE OF BY INCINERATION OR LANDFILL
IN ACCORDANCE WITH ALL LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.