SAFETY DATA SHEET



1. Identification

Product identifier BEHR PREMIUM PLUS Interior Semi-Gloss Enamel - Ultra Pure White

Other means of identification

Product number 3050

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier Behr Process Corp.

1801 E. St. Andrew Place Santa Ana. CA 92705

 Telephone
 714-545-7101

 Emergency telephone
 +1 760 476 3962

+1 866 519 4752

Access code 335213

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	10 - 30
Aluminum hydroxide	21645-51-2	0.5 - 1.5
Silicon dioxide, crystalline silica-free	7631-86-9	0.5 - 1.5

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard

Communication Standard.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

BEHR PREMIUM PLUS Interior Semi-Gloss Enamel - Ultra Pure White
950414 Version #: 03 Revision date: 12-March-2020 Issue date: 04-November-2019

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

IngestionRinse mouth. Get medical attention if symptoms occur.Most importantDirect contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

Treat symptomatically.

treatment needed

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media
Unsuitable extinguishing
media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

Move containers from fire area if you can do so without risk.

equipment/instructions
Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Type

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the

Value

Form

SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	1 01111
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910.	1000)		
Components	Туре	Value	Form
Silicon dioxide, crystalline TWA silica-free (CAS 7631-86-9)	TWA	0.8 mg/m3	
		20 mppcf	
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	Form
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Value	s		
Components	Туре	Value	Form
Aluminum hydroxide (CAS 21645-51-2)	TWA	1 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Chen	nical Hazards		
Components	Туре	Value	
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)	TWA	6 mg/m3	

Biological limit values

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear suitable protective clothing.

Respiratory protection If airborne concentrations are above the applicable exposure limits, use NIOSH approved

respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an

uncontrolled release, exposure levels are not known, or any other circumstances where

air-purifying respirators may not provide adequate protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical stateLiquid.FormLiquid.ColorWhite.OdorSlight.

Odor threshold Not available.

pH 7 - 10

Melting point/freezing point Not available.

Initial boiling point and boiling > 99 °F (> 37.2 °C)

range

Flash point

Not applicable.

Evaporation rate Not available.
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Not available. Vapor pressure Not available. Vapor density

1.26 Relative density

Solubility(ies)

Soluble Solubility (water)

Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available.

50 - 140 KU (25 °C) **Viscosity**

Other information

Density 10.50 lbs/gal **Explosive properties** Not explosive. Not oxidizing. Oxidizing properties

VOC 1 g/l (including water) (Material)

2 g/l (excluding water) (Coating)

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Contact with incompatible materials. Conditions to avoid

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation. Eye contact Direct contact with eyes may cause temporary irritation.

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Test Results Components **Species**

3-lodo-2-propynyl butylcarbamate (CAS 55406-53-6)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat 1 g/kg

BEHR PREMIUM PLUS Interior Semi-Gloss Enamel - Ultra Pure White Revision date: 12-March-2020 950414 Version #: 03 Issue date: 04-November-2019 Components Species Test Results

Aluminum hydroxide (CAS 21645-51-2)

Acute Oral

LD50 Rat > 5000 mg/kg

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Acute Dermal

LD50 Rabbit > 5000 mg/kg, 24 Hours

Inhalation

Dust

LC50 Rat > 0.14 mg/l, 4 Hours

Oral

LD50 Rat > 3300 mg/kg

Titanium dioxide (CAS 13463-67-7)

Acute Inhalation

LC50 Rat 3.43 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Inhalation of titanium dioxide dust may cause cancer, however due to the physical form of the

product, inhalation of dust is not likely.

IARC Monographs. Overall Evaluation of Carcinogenicity

Silicon dioxide, crystalline silica-free (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil This product is miscible in water.

Other adverse effects No data available.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

the IBC Code

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

3-lodo-2-propynyl butylcarbamate (CAS 55406-53-6)

950414 Version #: 03 Revision date: 12-March-2020 Issue date: 04-November-2019

BEHR PREMIUM PLUS Interior Semi-Gloss Enamel - Ultra Pure White

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Titanium dioxide (CAS 13463-67-7)

16. Other information, including date of preparation or last revision

04-November-2019 Issue date 12-March-2020 **Revision date**

Version # 03

HMIS® ratings Health: 0

Flammability: 0 Physical hazard: 0

List of abbreviations DOT: Department of Transportation (49 CFR 172.101).

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG Code: International Maritime Dangerous Goods Code.

LC50: Lethal Concentration, 50%.

LD50: Lethal Dose, 50%.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PEL: Permissible Exposure Limit. TWA: Time Weighted Average Value.

HSDB® - Hazardous Substances Data Bank References

Behr Process Corp cannot anticipate all conditions under which this information and its product, or **Disclaimer**

> the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

BEHR PREMIUM PLUS Interior Semi-Gloss Enamel - Ultra Pure White

SDS US 950414 Version #: 03 Revision date: 12-March-2020 Issue date: 04-November-2019 7/7