

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: Fusion Pro – Single Component Grout

Product Code: F2130 - F2155

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Use: Grout.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Custom Building Products

13001 Seal Beach Blvd

Seal Beach, CA

90740

Telephone Number: (562) 598-8808

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone INFOTRAC 1-800-535-5053 (US and Canada)

Number: INTERNATIONAL + 1-352-323-3500

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL ACCORDING TO OSHA HAZCOM 2012

Hazard class

Carcinogenicity 1A

Specific target organ toxicity - Repeated Exposure 1

Serious eve irritation 2A

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

Hazard Pictogram:





Signal Word: Danger

Hazard Statement: May cause cancer. Causes damage to lungs through prolonged or

repeated exposure. Causes serious eye irritation.

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe fumes/vapors. Wash hands thoroughly after handling. Do

not eat, drink or smoke when using this product.


Response: If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or

Print date: 2013-09-25

concerned: Get medical advice/attention.

Storage: Store locked up.





Disposal: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

2.3 ADDITIONAL INFORMATION

Hazards not otherwise classified: Not applicable.

13 % of the mixture consists of ingredient(s) of unknown acute toxicity.

WHMIS Classification(s):

Class D2A - Carcinogenicity

Class D2A - Teratogenicity and embryotoxicity

Class D2A - Chronic Toxic Effects

Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:



WHMIS Signal Word: CAUTION

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Ingredient	CAS No	Wt. %
Silica, crystalline, quartz	14808-60-7	60 - 100
p-[(Diiodomethyl)sulphonyl]toluene	20018-09-1	1 - 5
Ethanol	64-17-5	1 - 5
Ethylene glycol monobutyl ether	111-76-2	0.1 - 1
Ethylene glycol	107-21-1	0.1 - 1
Bentonite	1302-78-9	0.1 - 1

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Section 4: FIRST- AID MEASURES

4.1 DESCRIPTION OF THE FIRST AID MEASURE

Eye: In case of contact, immediately flush eyes with plenty of water for at

least 15 minutes. If easy to do, remove contact lenses, if worn. Get

medical attention immediately.

Skin: In case of contact, immediately flush skin with plenty of soap and

water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

Inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing. Get medical advice/attention if

you feel unwell.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by

medical personnel. Never give anything by mouth to an unconscious

person. Get medical advice/attention.





4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Eye: Causes serious eye irritation. Symptoms may include discomfort or

pain, excess blinking and tear production, with possible redness and

swelling.

Skin: May cause skin irritation. Symptoms may include redness, drying,

defatting and cracking of the skin.

Inhalation: May cause respiratory tract irritation. Causes damage to lungs

through prolonged or repeated exposure.

Ingestion: May cause stomach distress, nausea or vomiting.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

Note to Physicians: Symptoms may not appear immediately.

Specific Treatments: In case of accident or if you feel unwell, seek medical advice

immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Flammability: Not flammable by WHMIS/OSHA criteria.

5.2 EXTINGUISHING MEDIA

Suitable Extinguishing Media: Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available. Sensitivity to Static Discharge: Not available.

5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP


Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite),

then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Print date: 2013-09-25

Methods for Cleaning-Up: Scoop up material and place in a disposal container. Provide

ventilation.





Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Handling: Avoid contact with skin and eyes. Do not swallow. Handle and open

container with care. When using do not eat, drink or smoke. Do not

breathe fumes/vapors. (See section 8)

General Hygiene Advice: Launder contaminated clothing before reuse. Wash hands before

eating, drinking, or smoking.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Keep container tightly closed.

Store in a well-ventilated place. Do not store at temperatures above

49 °C / 120 °F. (See section 10)

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Exposure Guidelines

Occupational Exposure Limits				
Ingredient	OSHA-PEL	ACGIH-TLV		
((10 mg/m³)/(%SiO ₂ +2) (resp)) ((30 mg/m³)/(%SiO ₂ +2) (total))				
Silica, crystalline, quartz	((250)/(%SiO ₂ +5) mppcf (resp))	0.025 mg/m³		
p-[(Diiodomethyl)sulphonyl]toluene	Not available	Not available		
Ethanol	1000 ppm	1000 ppm		
Ethylene glycol monobutyl ether	50 ppm	20 ppm		
Ethylene glycol	50 ppm	50 ppm		
Bentonite	Not available	Not available		

8.2 EXPOSURE CONTROLS

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust,

fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTIVE MEASURES

Personal Protective Equipment:

Eye/Face Protection: Safety glasses or goggles are recommended when using product.

Skin Protection:

Hand Protection: Wear chemical-resistant gloves.

Body Protection: Wear suitable protective clothing, including appropriate boots,

boot covers, overshoes, etc., as may be appropriate.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the


selected respirator.

General Health and Safety

Measures:

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Wash

contaminated clothing before reusing.







Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Not available.

Color: Various.

Odor: Not available.
Odor Threshold: Not available.

Physical State: Solid.

pH: 9.0 – 9.5

Melting Point/Freezing Point:Not available.Initial Boiling Point and Boiling Range:Not available.

Flash Point: > 100°C (> 212°F)

Evaporation Rate: Not available. Flammability: Not flammable. **Lower Flammability/Explosive Limit:** Not available. **Upper Flammability/Explosive Limit:** Not available. **Vapor Pressure:** Not available. Vapor Density: Not available. Relative Density/Specific Gravity: Not available. Solubility: Not available.

Partition coefficient: n-octanol/water: Not available.

Auto-ignition Temperature: Not available.

Decomposition Temperature: Not available.

Viscosity: 900K - 1.3 million cPs (21°C / 70°F)

Oxidizing Properties: Not available.

Explosive Properties: Not available.

VOC content, g/L: 54 g/L (1.8% - Method 310)

Section 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2 CHEMICAL STABILITY


Stable under normal storage conditions.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

10.4 CONDITIONS TO AVOID

Heat. Incompatible materials.





10.5 INCOMPATIBLE MATERIALS

None known.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Symptoms related to physical/chemical/toxicological characteristics:

Eye: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

May cause skin irritation. Symptoms may include redness, drying,

defatting and cracking of the skin.

Ingestion: May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation. Causes damage to lungs through

prolonged or repeated exposure.

Acute Toxicity:

Ingredient	LC50	LD50
0.11.	N. 7. 11	O 1400 / (TD)
Silica, crystalline, quartz	Not available.	Oral 120 g/kg, rat (TD _{lo})
p-[(Diiodomethyl)sulphonyl]toluene	Not available.	Not available.
Ethanol	Inhalation 124.7 mg/L 4 h, rat	Oral 7060 mg/kg, rat
		Oral 470 mg/kg, rat
	Inhalation 2.21 mg/L 4 h, rat	Dermal 2270 mg/kg, rat
Ethylene glycol monobutyl ether	Inhalation 450 ppm 4 h, rat	Dermal 220 mg/kg, rabbit
		Oral 4000 mg/kg, rat
Ethylene glycol	Inhalation > 2.5 mg/L 6hr, rat	Dermal 9530 µL/kg, rabbit
Bentonite	Not available.	Oral >5000 mg/kg, rat

Calculated overall Chemical Acute Toxicity Values		
LC50 (inhalation) LD50 (oral) LD50 (dermal)		
>5 mg/L 4h, rat	>2000 mg/kg, rat	>2000 mg/kg, rabbit

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Silica, crystalline, quartz	G-A2, I-1, N-1, O, CP65
p-[(Diiodomethyl)sulphonyl]toluene	Not listed.
	G-A3, I-1**, CP65**, O
Ethanol	**(in alcoholic beverages)
Ethylene glycol monobutyl ether	G-A3, I-3
Ethylene glycol	G-A4
Bentonite	Not listed.





11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation: May cause skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory Sensitization:

Based on available data, the classification criteria are not met.

Skin Sensitization:

Based on available data, the classification criteria are not met.

STOT-Single Exposure:

Based on available data, the classification criteria are not met.

Chronic Health Effects:

Carcinogenicity: May cause cancer.

Germ Cell Mutagenicity: Based on available data, the classification criteria are not met.

Reproductive Toxicity:

Developmental: Based on available data, the classification criteria are not met.

Teratogenicity: Hazardous by WHMIS criteria. **Embryotoxicity:** Hazardous by WHMIS criteria.

Fertility: Based on available data, the classification criteria are not met.

STOT-Repeated Exposure: Causes damage to lungs through prolonged or repeated exposure.

Aspiration Hazard: Based on available data, the classification criteria are not met.

Toxicologically Synergistic

Materials:Not available.Other Information:Not available.

Section 12: ECOLOGICAL INFORMATION

12.1 ECOTOXICITY

Acute/Chronic Toxicity: May cause long-term adverse effects in the aquatic environment.

12.2 PERSISTENCE AND DEGRADABILITY

Not available.

12.3 BIOACCUMULATIVE POTENTIAL

Bioaccumulation: Not available.

12.4 MOBILITY IN SOIL

Not available.

12.5 OTHER ADVERSE EFFECTS

Not available.

Section 13: DISPOSAL CONSIDERATIONS


13.1 WASTE TREATMENT METHODS

Disposal Method: This material must be disposed of in accordance with all

local, state, provincial, and federal regulations.

Print date: 2013-09-25

Other disposal recommendations: Not available.





Section 14: TRANSPORT INFORMATION

14.1 UN NUMBER

DOT TDG

Not regulated. Not regulated.

14.2 UN PROPER SHIPPING NAME

DOT TDG

Not applicable. Not applicable.

14.3 TRANSPORT HAZARD CLASS (ES)

DOT TDG

Not applicable. Not applicable.

14.4 PACKING GROUP

DOT TDG

Not applicable. Not applicable.

14.5 ENVIRONMENTAL HAZARDS

Not available.

14.6 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available.

14.7 SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SARA Title III				
Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
p-[(Diiodomethyl)sulphonyl]toluene	Not listed.	Not listed.	Not listed.	Not listed.
Ethanol	Not listed.	Not listed.	Not listed.	Not listed.
Ethylene glycol monobutyl ether	Not listed.	Not listed.	Not listed.	Yes.
Ethylene glycol	Not listed.	Not listed.	5,000	313
Bentonite	Not listed.	Not listed.	Not listed.	Not listed.





State Regulations

California Proposition 65:

This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. (Silica, crystalline; Titanium dioxide; 1,4-Dioxane; Ethylene oxide; Ethyl acrylate; N-Methylolacrylamide; Acetaldehyde; Acrylamide)

Global Inventories:

Ingredient	Canada DSL/NDSL	USA TSCA
Silica, crystalline, quartz	DSL	Yes.
p-[(Diiodomethyl)sulphonyl]toluene	DSL	Yes.
Ethanol	DSL	Yes.
Ethylene glycol monobutyl ether	DSL	Yes.
Ethylene glycol	DSL	Yes.
Bentonite	DSL	Yes.

NFPA National Fire Protection Association:		
Health: 1		
Fire:	0	
Reactivity:	0	

HMIS-Hazardous Materials Identification System		
Health: 1*		
Fire:	0	
Physical Hazard:	0	

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65 California Proposition 65

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

Print date: 2013-09-25

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.


1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Date of Preparation: September 25, 2013

Version: 1.0





Revision Date: September 25, 2013

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Nexreg Compliance Inc.

Phone: (519) 488-5126

www.nexreg.com

Prepared for: Custom Building Products

End of Safety Data Sheet

