

Supersedes Date 11/12/2008

Issuing Date 04/01/2011

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name T-LUBE PLUS AEROSOL
 Recommended use Lubricant
 Information on Manufacturer
 CERTIFIED LABS, DIV. OF NCH CORP.
 BOX 152170
 IRVING, TEXAS 75015

Product Code 5496
 Chemical nature Resins in solution
 Emergency Telephone Number
 CHEMTREC 1-800-424-9300

2. HAZARDS IDENTIFICATION

Emergency Overview
DANGER!
 Extremely flammable
 May cause skin irritation
 Causes eye irritation
 May be harmful if inhaled
 May be harmful if swallowed

Color white

Physical State Liquid

Odor Rubbing alcohol

Potential Health Effects

Principle Route of Exposure

Inhalation, Skin contact, Eye contact.

Primary Routes of Entry

Inhalation

Acute Effects

Eyes

Causes eye irritation.

Skin

May cause skin irritation.

Inhalation

May cause irritation of respiratory tract. Inhalation may cause central nervous system effects. May cause central nervous system depression. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. May be fatal if inhaled in large quantities.

Ingestion

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Toxicity

May cause polymer fume fever, a temporary flu-like illness accompanied by chills, fever, and a cough. This can last up to 24 hours in duration. Prolonged or repeated exposure increases the risk. Liver and kidney injuries may occur.

Target Organ Effects

Eyes, Skin, Respiratory system, Central nervous system, Liver, Kidney.

Aggravated Medical Conditions

Skin disorders, Respiratory disorders, Neurological disorders, Liver disorders, Kidney disorders.

Potential Environmental Effects

See Section 12 for additional Ecological Information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS-No
Isopropyl alcohol	67-63-0
Butane	106-97-8
Propane	74-98-6
Polytetrafluoroethylene	9002-84-0

4. FIRST AID MEASURES

General Advice

Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists.

Eye Contact

Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation develops and persists.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash contaminated clothing before re-use.

Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion

Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention if symptoms occur. Never give anything by mouth to an unconscious person.

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flash Point 53 °F / 12 °C

Method

Set a closed cup

Autoignition Temperature No information available.

Upper 12.7

Lower 1.8

Flammability Limits in Air %

Suitable Extinguishing Media

Foam. Alcohol-resistant foam. Dry chemical. Water spray. Carbon dioxide (CO₂).

Unsuitable Extinguishing Media

None known.

Specific hazards arising from the chemical

Solvent vapors are heavier than air and may spread along floors. Vapors may ignite and explode. Flame extension: 30 inches / 75 cm and Burnback: 0 inches / 0 cm.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Aerosol Level (NFPA 30B) -

3

NFPA Health 2

Flammability 4

Instability 0

HMIS Health 2

Flammability 4

Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation. Prevent further leakage or spillage if safe to do so. Material can create slippery conditions.

Environmental Precautions

Do not flush into surface water or sanitary sewer system.

Methods for Containment

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Methods for Cleaning Up

Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers.

Neutralizing Agent

Not applicable.

7. HANDLING AND STORAGE

Handling	Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist or gas.			
Storage	Keep away from heat and sources of ignition.			
Storage Temperature	Minimum	35 °F / 2 °C	Maximum	120 °F / 49 °C
Storage Conditions	Indoor	X	Outdoor	Heated Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 980 mg/m ³	IDLH: 2000 ppm STEL 500 ppm STEL 1225 mg/m ³ TWA: 400 ppm TWA: 980 mg/m ³
Butane	TWA: 1000 ppm	No data available	TWA: 800 ppm TWA: 1900 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Polytetrafluoroethylene	No data available	No data available	No data available

Engineering Measures Ensure adequate ventilation, especially in confined areas. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal Protective Equipment
Eye/Face Protection Safety glasses with side-shields.
Skin Protection For prolonged or repeated contact, use protective gloves
Respiratory Protection In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid	Viscosity	Slight Viscous
Color	white	Odor	Rubbing alcohol
Appearance	Cloudy	pH	Not applicable
Specific Gravity	0.69	Evaporation Rate	51.6
Percent Volatile (Volume)	99.7	VOC Content (%)	99.0
VOC Photoreactive (Y/N)	Yes	Vapor Pressure	1301 mmHg @ 70°F
Vapor Density	1.9	Solubility	Moderately soluble
Boiling Point/Range	180 °F / 82 °C		

10. STABILITY AND REACTIVITY

Chemical Stability	Stable. Hazardous polymerization does not occur.
Conditions to Avoid	Keep away from open flames, hot surfaces, and sources of ignition
Incompatible Products	Strong oxidizing agents, Strong acids.
Hazardous Decomposition Products	Carbon oxides, Hydrogen fluoride, Fluorinated hydrocarbons.
Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Product Information No information available.

Component Information No information available

Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
Isopropyl alcohol	= 4386 mg/kg (Rat)	= 12800 mg/kg (Rat) = 12870 mg/kg (Rabbit)	= 72.6 mg/L (Rat) 4 h	no data available	no data available
Butane	no data available	no data available	= 658 mg/L (Rat) 4 h	no data available	no data available
Propane	no data available	no data available	= 658 mg/L (Rat) 4 h	no data available	no data available
Polytetrafluoroethylene	no data available	no data available	= 45 mg/m ³ (Rat) 30 min	no data available	no data available

Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Isopropyl alcohol	no data available	no data available	no data available	no data available	eyes, respiratory system, skin, liver, kidney, CNS
Butane	no data available	no data available	no data available	no data available	CNS
Propane	no data available	no data available	no data available	no data available	CNS
Polytetrafluoroethylene	no data available	no data available	no data available	no data available	no data available

Carcinogenicity There are no known carcinogenic chemicals in this product.

Component	ACGIH	IARC	NTP	OSHA	Other
Isopropyl alcohol	not applicable	not applicable	not applicable	not applicable	not applicable
Butane	not applicable	not applicable	not applicable	not applicable	not applicable
Propane	not applicable	not applicable	not applicable	not applicable	not applicable
Polytetrafluoroethylene	not applicable	not applicable	not applicable	not applicable	not applicable

12. ECOLOGICAL INFORMATION

Product Information No information available.

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
Isopropyl alcohol	EC50 > 1000 mg/L Desmodesmus subspicatus 72 h EC50 > 1000 mg/L Desmodesmus subspicatus 96 h	LC50 = 11130 mg/L Pimephales promelas 96 h LC50 = 9640 mg/L Pimephales promelas 96 h LC50 > 1400000 µg/L Lepomis macrochirus 96 h	EC50 = 35390 mg/L 5 min	= 13299 mg/L 48 h	0.05
Butane	no data available	no data available	no data available	no data available	2.63
Propane	no data available	no data available	no data available	no data available	2.3
Polytetrafluoroethylene	no data available	no data available	no data available	no data available	N/A

Persistence and Degradability No information available.
 Bioaccumulation No information available.
 Mobility No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal Dispose of in accordance with local regulations.
 Container Disposal Warning! Container under pressure. Do not puncture. Empty remaining contents.

14. TRANSPORT INFORMATION

DOT
 Proper Shipping Name Consumer commodity
 Hazard Class ORM-D
 Description Consumer commodity ,ORM-D,

TDG
 Proper shipping name Aerosols
 Hazard Class 2.1
 UN-No UN1950
 Description AEROSOLS,2.1,UN1950 LTD. QTY.

ICAO
 UN-No UN1950
 Proper Shipping Name Aerosols
 Hazard Class 2.1
 Shipping Description Aerosols,UN1950 LTD. QTY.

IATA
 UN-No UN1950
 Proper Shipping Name Aerosols, flammable
 Hazard Class 2.1
 ERG Code 10L
 Shipping Description UN1950,Aerosols, flammable,2.1 LTD. QTY.

IMDG/IMO
 Proper Shipping Name Aerosols
 Hazard Class 2.1
 UN-No UN1950
 EmS No. F-D, S-U
 Shipping Description UN1950, Aerosols,2.1 LIMITED QUANTITIES

15. REGULATORY INFORMATION

Inventories
 TSCA Complies
 DSL Complies

U.S. Federal Regulations

SARA 313
 Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Isopropyl alcohol	67-63-0	40-70	1.0 % de minimis concentration (only if manufactured by the strong acid process, no supplier notification)

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
Yes	Yes	Yes	Yes	No

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
Isopropyl alcohol	Not applicable	Not applicable
Butane	Not applicable	Not applicable
Propane	Not applicable	Not applicable
Polytetrafluoroethylene	Not applicable	Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class
 A Compressed gases, B5 Flammable aerosol, D2B Toxic materials.



16. OTHER INFORMATION

Prepared By	Mike McDowell
Supersedes Date	11/12/2008
Issuing Date	03/31/2011
Reason for Revision	No information available.
Glossary	No information available.
List of References.	No information available.

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.