# **Material Safety Data Sheet**



FACILIPRO PREMIUM LOW ODOR FLOOR FINISH STRIPPER Use Solution (4.2 - 12.5%)

### Section 1. Chemical product and company identification

Trade name : FACILIPRO PREMIUM LOW ODOR FLOOR FINISH STRIPPER Use Solution

(4.2 - 12.5%)

Supplier : Ecolab Inc. Institutional Division

370 N. Wabasha Street St. Paul, MN 55102 1-800-352-5326

**Code** : ut912544-03

Date of issue 10-November-2009

EMERGENCY HEALTH INFORMATION: 1-800-328-0026 Outside United States and Canada CALL 1-651-222-5352 (in USA)

#### Section 2. Hazards identification

Physical state : Liquid. [Liquid.]
Emergency : CAUTION!

overview

MAY CAUSE EYE AND SKIN IRRITATION.

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Potential acute health effects

Eyes : Moderately irritating to eyes.

Skin : Moderately irritating to the skin.

Inhalation : Slightly irritating to the respiratory system.Ingestion : No known significant effects or critical hazards.

See toxicological information (section 11)

## Section 3. Composition/information on ingredients

<u>Name</u>	CAS number	% by weight
2-hexyloxyethanol	112-25-4	1
BENZYL ALCOHOL	100-51-6	1 - 5
ETHANOLAMINE	141-43-5	1 - 5
POTASSIUM OLEATE	143-18-0	1 - 5

#### Section 4. First aid measures

Eye contact : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses and

flush again. Get medical attention if irritation persists.

**Skin contact**: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing

and shoes. Get medical attention if irritation persists. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

**Inhalation**: If inhaled, remove to fresh air.

**Ingestion**: Do not induce vomiting. Never give anything by mouth to an unconscious person. If irritation

persists, get medical attention.

FACILIPRO PREMIUM LOW ODOR FLOOR FINISH STRIPPER Use Solution (4.2 -

12.5%)

### Section 5. Fire-fighting measures

Flash point

: > 100°C

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

metal oxide/oxides

Fire-fighting media and

instructions

: Use an extinguishing agent suitable for the surrounding fire.

Dike area of fire to prevent runoff.

In a fire or if heated, a pressure increase will occur and the container may burst.

Page: 2/4

Special protective equipment :

for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

mode.

#### Section 6. Accidental release measures

Personal precautions

: Use suitable protective equipment (section 8). Do not allow to enter drains or watercourses.

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

: For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain it to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

#### Section 7. Handling and storage

Handling

: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Storage

: Keep out of reach of children. Keep container in a cool, well-ventilated area. Keep container

tightly closed.

#### Section 8. Exposure controls/personal protection

**Engineering measures** 

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protection:

Eves

: Eye protection recommended.

Hands

: For prolonged or repeated handling, use the following type of gloves: Impervious gloves.

Skin

: No protective equipment is needed under normal use conditions.

Respiratory

: A respirator is not needed under normal and intended conditions of product use.

<u>Name</u>

Exposure limits

**ETHANOLAMINE** 

ACGIH TLV (United States, 1/2009). STEL: 15 mg/m³ 15 minute(s).

STEL: 6 ppm 15 minute(s). TWA: 7.5 mg/m³ 8 hour(s). TWA: 3 ppm 8 hour(s).

OSHA PEL (United States, 11/2006).

TWA: 6 mg/m<sup>3</sup> 8 hour(s). TWA: 3 ppm 8 hour(s). FACILIPRO PREMIUM LOW ODOR FLOOR FINISH STRIPPER Use Solution (4.2 -

12.5%)

#### Section 9. Physical and chemical properties

Physical state : Liquid. [Liquid.]
Color : Hazy liquid. [Light]

Odor : Amine-like. pH : 12 to 13

Relative density : 1

#### Section 10. Stability and reactivity

Stability : The product is stable. Under normal conditions of storage and use, hazardous

polymerization will not occur.

Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition products

**products** should not be produced.

Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

### Section 11. Toxicological information

#### Potential acute health effects

Eyes : Moderately irritating to eyes.Skin : Moderately irritating to the skin.

Inhalation : Slightly irritating to the respiratory system.Ingestion : No known significant effects or critical hazards.

#### Potential chronic health effects

#### Other adverse effects

**Target organs**: Contains material which causes damage to the following organs: kidneys, liver.

Contains material which may cause damage to the following organs: upper respiratory

Page: 3/4

tract, central nervous system (CNS).

# Section 12. Ecological information

Ecotoxicity data : Not reported

#### Section 13. Disposal considerations

Waste disposal : The generation of

: The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority

requirements.

Waste : Unused product is D002 (Corrosive)

classification

Consult your local or regional authorities.

### Section 14. Transport information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

**UN Classification** 

**UN number** Not intended for

transport.

Proper shipping name Not available.

Class Not available.

Packing group -

FACILIPRO PREMIUM LOW ODOR FLOOR FINISH STRIPPER Use Solution (4.2 -Page: 4/4 12.5%)

See shipping documents for specific transportation information.

# Section 15. Regulatory information

**HCS Classification** : Irritating material

Target organ effects

U.S. Federal regulations

**SARA 313** 

California Prop. 65

**TSCA 8(b) inventory**: All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found.

SARA 302/304 emergency planning and notification: No products were found.

Form R - Reporting

**Product name** : 2-hexyloxyethanol **CAS** number 112-25-4

**Concentration** 1.3695 - 1.3975

requirements

: No products were found.

#### Section 16. Other information

**Hazardous Material** 

Information System (U.S.A.)



Date of issue : 10-November-2009. Responsible name **Regulatory Affairs** Date of previous issue : 15-May-2008.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.