

SECTION 1: Identification and Supplier/Manufacturer's Information

1.1. Product identifier

Product form: Mixture
 Product name: Erase Gel, Vandalism Mark Remover
 Product code: 10-517-02

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture: Vandalism Mark Remover

1.3. Details of the supplier of the safety data sheet

Pioneer Chemical T 310-366-7393
 13717 S. Normandie Ave. F 310-366-7193
 Gardena, CA 90249 - USA www.pioneerchem.com

1.4. Emergency telephone number

Emergency number: INFOTRAC: 800-535-5053

SECTION 2: Hazards identification


2.1. Classification of the substance or mixture

Classification (GHS-US)

Flammable aerosols	Category 1
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity, single exposure	Category 3 narcotic effects
Specific target organ toxicity, repeated exposure	Category 2
Aspiration hazard	Category 1

2.2. Label elements

GHS-US labeling

Hazard pictograms:  Hazard statements: Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.



Signal word: Danger Precautionary statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response: If swallowed: Immediately call a poison center/doctor. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Hazard not otherwise classified (HNOC)

None known.

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Toluene	(CAS No) 108-88-3	20 - 40
2-Butoxyethanol	(CAS No) 111-76-2	2.5 - 10
Acetone	(CAS No) 67-64-1	2.5 - 10
Butane	(CAS No) 106-97-8	2.5 - 10
Diethylene Glycol Monobutyl Ether	(CAS No) 112-34-5	2.5 - 10
Propane	(CAS No) 74-98-6	2.5 - 10
9-Octadecenoic	(CAS No) 112-08-1	1 - 2.5
Sodium Hydroxide	(CAS No) 1310-73-2	.01 - 1
Other componets below reportable levels		20 - 40

* Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact: Wash off with soap and water. Get medical attention if irritation develops and persists.

First-aid measures after eye contact: Rinse with water. Get medical attention if irritation develops and persists.

First-aid measures after ingestion: Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. If exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Powder. Foam. Carbon dioxide (CO2)

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

5.3. Advice for firefighters

Special protective equipment and precautions: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA

Fire-fighting equipment/instructions: Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder to monitor nozzles, if possible. If not withdraw and let fire burn out.

Specific methods: Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards: Extremely flammable aerosol

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of SDS.

6.2. Environmental precautions

Avoid releases to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustible (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has disposal, see section 13 of the SDS.

6.4. Reference to other sections

See Heading 8: Exposure controls and personal protection.

See Heading 10: Stability and reactivity

See Heading 13: Disposal Consideration

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

US. OSHA Table Z-1 Limits for Air Contaminates (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3
Acetone (CAS 67-64-1)	PEL	50 ppm 2400 mg/m3
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm
Sodium Hydroxide (CAS 1310-73-2)	PEL	1000 ppm 2 mg/m3

US. OSHA Table Z-2 (29 CFR 1910.1000)

Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

2-Butoxyethanol (CAS 111-76-2)	Ceiling	300 ppm
	TWA	200 ppm
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	1000 ppm 2 mg/m3
Butane (CAS 106-97-8)	STEL	1000 ppm
Diethylene Glycol Monobutyl Ether (CAS 112-34-5)	TWA	10 ppm

US ACGIH Threshold Limit Values

Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3
Acetone (CAS 67-64-1)	TWA	5 ppm 590 mg/m3 250 ppm
	TWA	1900 mg/m3 800 ppm
Propane (CAS 106-97-8)	TWA	1800 mg/m3 1000 ppm
Sodium Hydroxide (CAS 1310-73-2)	STEL	560 mg/m3
Toluene (CAS 108-88-3)	STEL	560 mg/m3
	TWA	375 mg/m3 100 ppm

8.2. Exposure controls

US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2)	Skin designation applies.
Toluene (CAS 108-88-3)	Skin designation applies.

US - Tennessee OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)	Can be absorbed through the skin.
--------------------------------	-----------------------------------

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2)	Can be absorbed through the skin.
--------------------------------	-----------------------------------

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2)	Can be absorbed through the skin.
--------------------------------	-----------------------------------

Appropriate engineering controls:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to condition. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If

exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

8.3. Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Hand protection	Wear appropriate chemical resistant gloves.
Skin protection other skin protection	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filterer / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Gas.	Relative evaporation rate (butyl acetate=1):	No data available
Color:	Tan	Partition Coefficient n-Octanol-Water:	No data available
Odor:	Solvent	Flammability (solid, gas):	No data available
		Flammability limit - lower (%)	1.90%
		Flammability limit - upper (%)	9.50%
Odor threshold:	No data available	Vapor pressure:	60 - 75 psig @ 70F estimated
pH:	12.5 - 13.4 estimated	Vapor density:	No data available
Melting point:	No data available	Specific Gravity @ 77° F:	1.012 - 1.032
Freezing point:	No data available	Solubility:	No data available
Boiling point:	193.64 °F (89.8 °C estimated)	Flash point:	-156.0 °F (-104.4 °C)
Evaporation rate:	No data available		Propellant estimated
Viscosity:	No data available	Auto-ignition temperature:	No data available
		Decomposition temperature:	No data available

9.2. Other information

Specific gravity .0765 estimated

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts violently with strong acids. This product may react with oxidizing agents.

10.2. Chemical stability

Material is stable under normal conditions

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

Avoid temperatures exceeding the flash point. Do not mix with other chemicals. Contact with incompatible materials

10.5. Incompatible materials

Acids. Strong oxidizing agents. Oxidizing agents. Nitrates. Fluorine. Chlorine.

10.6. Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects. Prolonged inhalation may be harmful.
Skin contact	Cause skin irritation. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Eye contact	Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling and blurred vision. Skin irritation. May cause redness and pain.
Acute toxicity	May be fatal if swallowed and enters airways. Narcotic effects.

2-Butoxyethanol (CAS 111-76-2)

LD50 dermal guinea pig	230 ml/kg, 24 hrs 7.3 ml/kg, 4 days
LD50 dermal rabbit	450 ml/kg, 24 hrs 435 mg/kg, 24 hrs
	0.63 ml/kg
LD50 dermal rat	> 2000 mg/kg, 24 hrs

LC50 inhalation rabbit	400 ppm, 7 hrs
LC50 inhalation rat	450 ppm, 4 hrs
LD100 oral rabbit	695 mg/kg
LD50 oral dog	> 695 mg/kg
LD50 oral guinea pig	1200 mg/kg
LD50 oral rat	530 - 2800 mg/kg
Acetone (CAS 67-64-1)	
LD50 dermal guinea pig	> 7426 mg/kg, 24 hrs > 9.4 ml/kg, 24 hrs
LD50 dermal rabbit	> 7426 mg/kg, 24 hrs > 9.4 ml/kg, 24 hrs
LC50 inhalation rat	55700 ppm, 3 hrs 132 mg/l, 3 hrs 50.1 mg/l
LD50 oral rat	5800 mg/kg 2.2 ml/kg
Butane (CAS 106-97-8)	
LC50 inhalation mouse	1237 mg/l, 120 minutes 52 %, 120 minutes
LC50 inhalation rat	1355 mg/l
Diethylene Glycol Monobutyl Ether (CAS 112-34-5)	
LD50 dermal guinea pig	2 ml/kg, 2 days
LD50 dermal rabbit	2764 mg/kg, 24 hrs
LD100 oral rabbit	4000 mg/kg
LD50 oral guinea pig	2000 mg/kg
LD50 oral mouse	2410 mg/kg
LD50 oral rabbit	2500 - 3000 mg/kg
LD50 oral rat	3306 mg/kg
Propane (CAS 74-98-6)	
LC50 inhalation mouse	1237 mg/l, 120 minutes 52 %, 120 minutes
LC50 inhalation rat	1355 mg/l 658 mg/l/4h
Sodium Hydroxide (CAS 1310-73-2)	
LD50 dermal rat	1350 mg/kg
Toluene (CAS 108-88-3)	
LD50 dermal rabbit	> 5000 mg/kg, 24 hrs
LC50 inhalation mouse	6405 - 7436 ppm, 6 hrs 5320 ppm, 8 hrs
LC50 inhalation rat	5879 - 6281 ppm, 6 hrs 12.5 - 28.8 mg/l, 4 hrs
LD50 oral rat	5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation:	Causes skin irritation
Serious eye damage/irritation:	Causes serious eye irritation.
Respiratory or skin sensitization:	This product is not expected to cause skin sensitization.
Germ cell mutagenicity:	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity:	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA
Reproductive toxicity:	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure):	May cause drowsiness and dizziness.
Specific target organ toxicity (repeated exposure):	Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Liver. May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard:	May be fatal if swallowed and enters airways.
Chronic effects:	Prolonged inhalation may be harmful. May be Harmful if absorbed through skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

May cause damage to organs through prolonged or repeated exposure.

SECTION 12: Ecological information

12.1. Toxicity

2-Butoxyethanol (CAS 111-76-2)

LC50 fish 1250 mg/l, 96 hours (Inland silverside (Menidia beryllina))

9-Octadecenoic Acid (CAS 112-80-1)

LC50 fish 205 mg/l, 96 hours (Fathead minnow (Pimephales promelas))

Acetone (CAS 67-64-1)

EC50 Crustacea 21.6 - 23.9 mg/l, 48 hours (Water flea (Daphnia Magna))

LC50 fish 4740 - 6330 mg/l, 96 hours

Diethylene Glycol Monobutyl Ether (CAS 112-34-5)

LC50 Fish 1300mg/l, 96 hours (Bluegill (Lepomis macrochirus))

Sodium Hydroxide (CAS 1310-73-2)

EC50 Crustacea 21.6 - 23.9 mg/l, 48 hours (Water flea (Daphnia Magna))

LC50 fish 45, 96 hours Fish

Toluene (CAS 108-88-3)

IC50 Algae 433.0001 mg/l, 72 hours Algae

EC50 Crustacea 21.6 - 23.9 mg/l, 48 hours (Water flea (Daphnia Magna))

LC50 fish 8.11 mg/l, 96 hours (Coho salmon, silver salmon (Oncorhynchus kisutch))

* Estimates for product may be based on additional component data not shown.

12.2. Persistence and degradability

No data is available on the degradability of this product.

12.3. Bioaccumulative potential

No data available

12.4. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, gloval warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal instructions:

Content and remain or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations:

Dispose in accordance with all applicable regulations.

Hazardous waster code:

The waste code should be assigned in discussion between the user, the producer and the waster disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1) U002

Toluene (CAS 108-88-3) U220

Waste from residues / unused products:

Dispose of in accordance with local regulations. Empty containers or liners may retain come product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions)

Contaminated packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

SECTION 14: Transport information

UN-No.(DOT):

UN1950

UN proper shipping name

Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) 2.1

Packing group

Not applicable

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

Special provisions

N82

Packaging exceptions

306

Packaging non bulk None
Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

DOT



SECTION 15: Regulatory information

15.1. US Federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)	Listed.
Sodium Hydroxide (CAS 1310-73-2)	Listed.
Toluene (CAS 108-88-3)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorizations Act of 1986 (SARA)

Hazard Categories	Immediate Hazard - Yes
	Delayed Hazard - Yes
	Fire Hazard - Yes
	Pressure Hazard - No
	Reactivity Hazard - No

SARA 302 Extremely Hazardous Substance

Not listed.

SARA 311/312 Hazardous chemical

No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Toluene	108-88-3	20 - 40

15.2. Other Federal Regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112® Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-697-8)
Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA)

Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1)	6532
Toluene (CAS 108-88-3)	6594

Drug Enforcement Administration (DEA). List 1 & 2, Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1)	35% WV
Toluene (CAS 108-88-3)	35%WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)	6532
Toluene (CAS 108-88-3)	594

15.3. US State regulations

US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2)
 Acetone (CAS 67-64-1)
 Butane (CAS 106-97-8)
 Propane (CAS 74-98-6)
 Sodium Hydroxide (CAS 1310-73-2)
 Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2)
 Acetone (CAS 67-64-1)
 Butane (CAS 106-97-8)
 Propane (CAS 74-98-6)
 Sodium Hydroxide (CAS 1310-73-2)
 Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2)
 9-Octadecenoic Acid (CAS 112-80-1)
 Acetone (CAS 67-64-1)
 Butane (CAS 106-97-8)
 Propane (CAS 74-98-6)
 Sodium Hydroxide (CAS 1310-73-2)
 Toluene (CAS 108-88-3)

US. Rhode Island TRK

Acetone (CAS 67-64-1)
 Butane (CAS 106-97-8)
 Propane (CAS 74-98-6)
 Sodium Hydroxide (CAS 1310-73-2)
 Toluene (CAS 108-88-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3)

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

15.4. International Inventories

Country(s) or region	Inventory Name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substance List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION 16: Other information

Disclaimer

This document is generated for the purpose of distributing health, safety, and environmental data. The information and recommendations are presented in good faith and believed to be from reliable sources, however, the information is provided without any warranty, expressed or implied, regarding its completeness or accuracy. Some information is from sources other than direct test data on the material itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and for this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of the product.

ALL NON-EMERGENCY QUESTIONS SHOULD BE DIRECTED TO CUSTOMER SERVICE (310) 366-7393

Revision date: 4/27/2016 Supersedes: 3/16/2006 Version: 2